



MATERIAL SAFETY DATA SHEET

INTEGRITY GEL SYSTEM: GEL CLEANSER

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: INTEGRITY GEL CLEANSER

PRODUCT CODES: INMIGG

MANUFACTURER: International Nail Manufacturers (inm)
Division of Nail Cartel, Inc.

ADDRESS: 1221 N. Lakeview Ave.
Anaheim, CA 92807

EMERGENCY PHONE: INFOTRAK: 1-800-535-5053

OTHER CALLS: 1-800-541-9838

FAX PHONE: 1-714-779-9971

CHEMICAL NAME: Glacial Methacrylic Acid

PREPARED BY: Steven Tate, Production Manager
1-714-779-9892

Chemical Identity CAS Numbers EINECS# INCI Name Exposure

OSHA

Limits

ACGIH

Carcinogen %

TWA/STEL TWA/STEL IARC/NTP/OSHA

Isopropyl Alcohol 67-63-0 200-661-7 Isopropyl Alcohol 400 ppm 400 ppm Not Listed 80-90

Ethyl Acetate 141 - 78 - 6 205-500-4 Ethyl Acetate 400 ppm 400 ppm Not Listed 10-20

Peach Oil 8002-78-6 N/E Prunus Persica (Peach)

Kernel Oil

N/E N/E Not Listed 0-1

N/E - None Established

N/R - Not Reviewed

N/DA - No Data Available

N/A - Not Applicable

Hazard Symbols: Xn, F **Risk Phrases:** R11, R20/22, R36/37/38 **Safety Phrases:** S7/9, S16, S24/25, S33, S37/39, S45

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- **Flammable liquid and vapor!**
- May cause eye irritation.
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.
- Please read entire MSDS for additional information.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Inhalation, skin and ingestion.

Eye Vapors are irritating to the eyes. Splashes may cause severe irritation, with stinging, tearing, redness, and pain with possible corneal damage.

Skin Repeated/prolonged contact may cause drying of skin. Symptoms include redness, burning, drying, cracking and skin burns.

Ingestion Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing

large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

Inhalation Vapors are irritating to nasal passages and throat and may cause stupor or headache. Symptoms usually occur at air concentrations higher than the recommended exposure limits.



Sub-Chronic Effects

Significant exposure to this chemical may adversely affect people with chronic disease or may cause damage to the respiratory system, skin and eyes.

NOTE: Refer to Section 11, Toxicological Information for Details

First Aid for Eye If symptoms develop move individual away from exposure and into fresh air. Flush eyes for 15 min.

with clean water while holding eyelids apart. If symptoms persist, seek medical attention.

First Aid for Skin Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.

First Aid for Ingestion If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side

with head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

First Aid for Inhalation Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give

MATERIAL SAFETY DATA SHEET INTEGRITY GEL SYSTEM: GEL CLEANSER

artificial respiration. Seek medical attention if discomfort persists.

Flash Point(°F/°C) Flammable Limit(vol%) Auto-ignition Temperature(vol%)

50°F/10°C LEL: 2 % ; UEL: 11.4 % N/DA

Method:

Extinguishing Media: Use CO₂, dry chemical for small fires, or alcohol type aqueous film forming foam.

Fire Fighting Instructions: If potential for exposure to vapors or products of combustion, wear complete personal

protective equipment including self contained breathing apparatus, with full face operated in pressure demand. Fight fire from a safe distance/protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. Vapor is heavier

than air and can travel considerable distance to source of ignition and flash back. Material creates a special hazard if it floats on water.

Spill or Release

Procedures

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU



Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Handling Closed containers exposed to temperature above (120°F) in transit or storage may develop vapor pressure. Open containers slowly. Ground all metal containers when transferring material. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking.

Storage Store in a cool, well ventilated area away from heat, sparks and flame. Keep containers closed when not in use.

Explosion Hazard Flammable liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Engineering

Controls

Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face

Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other

type of safety glasses.

Skin Protection Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit.

Neoprene and Nitrile rubber is better than PVC..

Respiratory

Protection

A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under

certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by

air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline

respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.



MATERIAL SAFETY DATA SHEET INTEGRITY GEL SYSTEM: GEL CLEANSER

Appearance Odor & Odor Threshold pH Specific Gravity Viscosity % Volatile

Clear, colorless, mobile liquid fruity, pungent mix odor N/A (H₂O = 1): N/A W/W % : 99+

Boiling Point/

Freezing Point

Decomposition

Temperature

Octanol/Water

Partitioning Coefficient

Log Po/w

Vapor

Pressure:

Vapor

Density

Evaporation

Rate Ignition

Solubility

In Water

(20°C)

77°C N/DA N/DA 73 mm Hg

@20°C

(Air=1):

3.0

(Butyl

Acetate=1): 4.5

N/A 8.7 %

Flash Point(°F/°C) Flammable Limit(vol%) Auto-ignition Temperature(vol%)

50°F/10°C LEL: 2 % ; UEL: 11.4 % N/DA

Stability: Incompatibility (Materials to Avoid):

Stable Oxidizing Agent i.e. Hydrogen peroxide , Nitric Acid ,
Perchloric Acid, Chromium Trioxide

Hazardous Decomposition Products:

Carbon Monoxide **Hazardous Polymerization:**

Will not occur

Conditions to Avoid:

Heat, flames, ignition sources, and incompatibles

Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity Irritation – skin Irritation - Eye

Mouse: LD50=3600 mg/kg N/DA Rat=1030 ug/m3/16W Skin, rabbit: LD50=12800 mg/kg N/DA

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the aliphatic

hydrocarbons. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization Mutagenicity Sub-chronic Toxicity

No information available Rat = 1030 ug/m3/16W No information available

Ecotoxicological Information

Acute Toxicity to Fish



Acute Toxicity to Invertebrates

Acute Toxicity to Algae

Bioconcentration Toxicity to Sewage

Bacteria

The LC50/96-hour values for fish are over 100 mg/l.

No information available No information available

No information available

No information available

Chemical Fate Information

Biodegradability When released into the soil, this material is expected to quickly evaporate. When released into the soil, this material may leach into groundwater. When released into the soil, this material may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate.

Chemical Oxygen Demand No information available

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do

not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing,

use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal

regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer

**MATERIAL SAFETY DATA SHEET
INTEGRITY GEL SYSTEM: GEL CLEANSER**

to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

DOT (49 CFR 172)

Proper Shipping Name: Flammable liquids, n.o.s., (isopropyl alcohol, ethyl acetate), 3, UN1993, PGII

Identification Number: UN1993

Marine Pollutant: No

Special Provisions: T8, T31

Emergency Response Guidebook (ERG) #: 128

IATA (DGR):

Proper Shipping Name: Flammable liquids, n.o.s., (isopropyl alcohol, ethyl acetate), 3, UN1993, PGII

Class or Division: 3



UN or ID Number: UN1993

Packaging Instructions:

Emergency Response Guidance (ICAO)#:

IMO (IMDG):

Proper Shipping Name: Flammable liquids, n.o.s., (isopropyl alcohol, ethyl acetate), 3, UN1993, PGII

Class or Division: 3.2

UN or ID Number: UN1993

Special Provisions & Stowage/Segregation: None

Emergency Schedule (EMS)#:

Other Information: Flash point = 10°C

US Federal Regulations

Clean Air Act: HAP/ODS This product contains the following hazardous air pollutants (HAP), as defined by the U. S.

Clean Air Act:

- NONE

This product does not contain any Class1 or Class 2 ODS.

Clean Water Act: Priority Pollutant This product contains the following Hazardous Substances as defined by the CWA:

- NONE

This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA.

FDA: Food Packaging Status This product has not been cleared by the FDA for use in food packaging and / or other

applications as an indirect food-packaging additive.

Occupational Safety and Health Act This product is considered to be hazardous under the OSHA Hazard Communication

Standard. It's hazards are:

- Immediate (acute) health hazard
- Fire hazard

RCRA This product contains the following chemicals considered to be hazardous waste under RCRA (40 CFR 261).

- Ethyl Acetate CAS# 141-78-6, RCRA Code: U112
- Characteristic of Ignitability, RCRA Code: D001

SARA Title III: Section 302 (TPQ) This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.

SARA Title III: Section 302 (RQ) This product contains chemicals regulated under Section 304 as extremely hazardous

chemicals for emergency release notification ("CERCLA" List):

- Ethyl Acetate CAS# 141-78-6, RQ (Lbs) 5000

SARA Title III: Section 311-312: This product is considered to be hazardous under the OSHA Hazard Communication

Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are:

- Immediate (acute) health hazard
- Fire hazard

SARA Title III: Section 313: This product contains the following chemicals which are subject to the reporting



MATERIAL SAFETY DATA SHEET INTEGRITY GEL SYSTEM: GEL CLEANSER

requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- Isopropyl Alcohol CAS# 67-63-0

TSCA Section 8(b): Inventory:

TSCA Significant New Use Rule:

This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

None of the chemicals in this material have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:

California No Significant Risk Rule:

Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

NONE

MA Right-to-Know Law: Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

NJ Right-to-Know Law: Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

PA Right-to-Know Law: Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

FL Right-to-Know Law: Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

MN Right-to-Know Law: Isopropyl Alcohol CAS #67-63-0, Ethyl Acetate CAS #141-78-6

International Regulations

CDSL: Canadian Inventory

(on Canadian Transitional List)

Isopropyl Alcohol CAS #67-63-0 is on the DSL list. WHMIS = B2, D2B

Ethyl Acetate CAS #141-78-6 is on the DSL list. WHMIS = B2, D2B

EINECS: European Inventory: **Eurocleanser:**

- HAZARD SYMBOLS: **Xn, F:** Harmful, Highly Flammable
- RISK PHRASES: **R11, highly flammable, R20/22: Harmful by inhalation and if swallowed, R36/37/38: Irritating to eyes, respiratory system and skin**
- SAFETY PHRASES: **S7/9: keep container tightly closed and in a well ventilated place, S16: keep away from sources of ignition- no smoking, S24/25: avoid contact with skin and eyes, S33: take precautionary measures against static discharges, S37/39: wear suitable gloves and eye/face protection, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)**

Hazard Rating System (Pictograms)

NFPA: HMIS:

1 3 0

Revised Sections since Last Version: Section 2 % changed from <, > to range, headers changed, format update

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the



materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

3

0 1

Flammability

Reactivity Health

Section 1 – Identification of the Substance/Preparation and of the